

Ludlow Bridge

Product code: AT1029 Product Finish: Chrome EAN13 barcode: 5060048380286




Product features:

- Metal & acrylic handle construction
- · Supplied with adjustable centre inlets
- · Fixing kit designed for thicker surface depths
- Quarter turn handle action for precise flow control
- · Custom designed for lower to mid pressures

Additional information / Parts included:

130 - 230mm centres

Product dimensions:



• Overall Height / projection: 400 mm

• Exit reach: 235 mm • Exit height: 260 mm • Centre distance(s):

• Base diameter(s): 50 mm

• Recommended hole diameter: Ø 35 mm

• Max. surface depth: 80 mm

• Spout diameter: 20 mm • Spout aerator size: 18f


Packaged properties:

Box length: 575mm Box depth: 75mm

Box width: 355mm Units per outer: 5

Tap only weight: 2.03kg Boxed weight: 2.66kg

Product flow characteristics:



- Min / Max water pressure: 0.20 / 5.5 bar
- Recommended / Max water temperature: 46°C / 70°C • Part G - Mixed flow rate at 3 bar (litres / min): 31.00
- Control valve type: Ceramic disc QT
- Product flow characteristics: Single flow
- Non return valve(s): Integral to hot & cold inlets
- Aerator type: Plastic mesh diffuser
- Accepts revolve / spray areator: No
- · Spout connection method: Locking collar
- Tail pipe inlet / outlet size: / 1/2" BSP Male
- Inlet pipe type / length: fixed threaded inlets / 120 mm

- Care instructions summary:

 Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after
- Warranty Summary (Full details available on request):

 Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year