

Gosford monobloc

Product code: AT1019 Product Finish: Chrome EAN13 barcode: 5060048380187




Product features:

- · Metal construction throughout
- · Custom designed for lower to mid pressures
- · Quarter turn handle action for precise flow control
- · Antisplash spout supplied as standard
- · Elegant minimalist design styling with a softened edge

Additional information / Parts included:

Product dimensions:



• Overall Height / projection: 390 mm

• Exit reach: 230 mm • Exit height: 245 mm Centre distance(s):

• Base diameter(s): 50 mm

• Recommended hole diameter: Ø 35 mm

• Max. surface depth: 60 mm

• Spout diameter: 24 mm • Spout aerator size: 22f


Packaged properties:

Box length: 430mm Box depth: 70mm

Box width: 340mm Units per outer: 5

Tap only weight: 1.92kg Boxed weight: 2.50kg

Product flow characteristics:



- Min / Max water pressure: 0.20 / 5.5 bar
- Recommended / Max water temperature: 46°C / 70°C • Part G - Mixed flow rate at 3 bar (litres / min): 18.40
- Control valve type: Ceramic disc QT • Product flow characteristics: Dual flow • Non return valve(s): No, none required
- Aerator type: Plastic mesh diffuser Accepts revolve / spray areator: Yes • Spout connection method: Grub screw
- Tail pipe inlet / outlet size: M12 / 15mm Ø
- Inlet pipe type / length: copper rigid tube / 245 mm

- Care instructions summary:

 Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

- Warranty Summary (Full details available on request):

 Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year