

Product Finish: Chrome

Product code: AT1145  
EAN13 barcode: 5060048381603




**Product features:**

- Metal & acrylic handle construction
- Custom designed for lower to mid pressures
- Fixing kit designed for thicker surface depths
- Elegant retro design form
- Quarter turn handle action for precise flow control

**Additional information / Parts included:**

Low pressure flow straightener included

**Product dimensions:**



- Overall Height / projection: 360 mm
- Exit reach: 235 mm
- Exit height: 210 mm
- Centre distance(s):


- Base diameter(s): 42 mm
- Recommended hole diameter: Ø 35 mm
- Max. surface depth: 55 mm

- Spout diameter: 20 mm
- Spout aerator size: 18f

**Packaged properties:**

<b>Box length:</b> 430mm	<b>Box depth:</b> 70mm
<b>Box width:</b> 340mm	<b>Units per outer:</b> 5
<b>Tap only weight:</b> 2.54kg	<b>Boxed weight:</b> 3.02kg

**Product flow characteristics:**



- Min / Max water pressure: 0.40 / 5.5 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G - Mixed flow rate at 3 bar (litres / min): 17.37

- Control valve type: Ceramic disc QT
- Product flow characteristics: Single flow
- Non return valve(s): Integral to hot & cold inlets

- Aerator type: Plastic mesh diffuser
- Accepts revolve / spray areator: No
- Spout connection method: Grub screw

- Tail pipe inlet / outlet size: / 1/2" BSP Male
- Inlet pipe type / length: fixed threaded inlets / 75 mm

**Care instructions summary:**

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

**Warranty Summary** (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year