

# Wall Mounted 2/3 Way Diverter Valve





### Product features:

- Metal & ABS construction
- Custom designed for lower range pressures
- · Luscious European quality chromium plate finish
- · Adjustable to suit various thickness of wall
- 5 year limited warranty


Packaged properties:

**Box length:** 250 mm **Box depth:** 85 mm **Box width:** 125 mm **Boxed weight:** 0.74 kg

Includes pop up waste?: No Additional comments:


ABS wall plate

#### **Product dimensions:**



- Overall Height / projection: 43 mm
- Exit reach:
- Exit height:
- Centre distance(s):
- Base diameter(s): 100 mm
  Product mounted where: Wall
  Recommended hole diameter:
  Min. fitting depth required: 50 mm
- Max. surface depth:

## **Product flow characteristics:**



- Min / Max water pressure: 0.5 / 5 bar
   Part G mixed flow rate at 3 bar (I/m): 23
- Max water temperature: 70° C
  Product flow characteristics:
- Aerator type:
- Includes output diverter?: Yes
  Control valve type: Diverter ()
  Non return valve position:
  Mesh particle filter size:
- Inlet / outlet size: 1/2" F / 1/2" F
  Inlet type / length: Fixed / mm
  Shower hose type / length:

### Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

### Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- Regular cleaning will prevent the build up of lime scale and dift
   After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives