abode

Exposed Thermostatic Shower Valve

Product features: Metal & ABS construction Custom designed for lower range pressures Thermostatic valve for safety & comfort · Supplied with adjustable centre inlets · Subtle soft sweeping design form Packaged properties: Includes pop up waste?: No Box length: 380 mm Additional comments: Box depth: 75 mm Box width: 175 mm Boxed weight: 2.23 kg Product dimensions: Overall Height / projection: 100 mm • Exit reach: • Exit height: Centre distance(s): 150 ± 20 mm 268 • Base diameter(s): 65 mm • Product mounted where: Wall Recommended hole diameter: • Min. fitting depth required: 60 mm • Max. surface depth: AB2105 v1 Euphoria low pressure thermostatic bar showe abode Product flow characteristics: • Min / Max water pressure: 0.2 / 5 bar Flow performance for model: AB2105 - Euphoria - Thermostatic low pressure bar shower n • Part G mixed flow rate at 3 bar (I/m): 32 • Max water temperature: 70° C • Product flow characteristics: • Aerator type: Includes output diverter?: No • Control valve type: Thermostatic () • Non return valve position: h&c inlet Mesh particle filter size: 0.60 mm Inlet / outlet size: 1/2" M / • Inlet type / length: Eccentric / 50 mm it water temperature = ma um achievable by sel note 1 note 2 Shower hose type / length: obode Warranty Summary (Full details available on request): Care instructions: Materials and workmanship defects warranted for 5 years Clean the mixers and showers regularly as required, using soap, do not use any other cleaners. Valves and working parts warranted for 5 years Regular cleaning will prevent the build up of lime scale and dirt After cleaning rinse thoroughly with clean water to remove any cleaner residue • Surface warranty defects warranted for 1 year Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean O-rings, hoses & gaskets warranted for 1 year water after using, avoid contact with any abrasives