

Product Finish: Chrome / black

Product code: AT2033
EAN13 barcode: 5060048383737




Product features:

- Innovative twist valve control feature
- Metal construction throughout
- Modern minimalism with flair
- Supplied complete with installation kit and filter cartridge
- Simple twist feature delivers filtered water

Additional information / Parts included:

Product dimensions:



- Overall Height / projection: 416 mm
- Exit reach: 215 mm
- Exit height: 252 mm
- Centre distance(s):


- Base diameter(s): 53 mm
- Recommended hole diameter: Ø 35 mm
- Max. surface depth: 65 mm

- Spout diameter: 24 mm
- Spout aerator size: 22f

Packaged properties:

- Box length: 580mm
- Box width: 350mm
- Box depth: 75mm
- Units per outer: 5
- Tap only weight: 3.78kg
- Boxed weight: 2.78kg

Product flow characteristics:



- Min / Max water pressure: 0.75 / 5.5 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G - Mixed flow rate at 3 bar (litres / min): 13.30

- Control valve type: Single lever ceramic cartridge, ceramic disc QT
- Product flow characteristics: (C&F / H) dual flow
- Non return valve(s): Hot & cold (integral to tails)

- Aerator type: Neoperl aerator honeycomb dual flow
- Accepts revolve / spray areator: No
- Spout connection method: Grub screw

- Tail pipe inlet / outlet size: M12 / 1/2" Male
- Inlet pipe type / length: flexible stainless braided hose / 260 mm

Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year