

Fervour








Product features:

- · Metal construction throughout
- Single lever control for effortless single handed control
- Luscious European quality chromium plate finish
- Supplied compete with flexible tail pipes for fast simple fitting
- · A modern design classic style

Packaged properties:

Box length: tbc mm Box depth: tbc mm Box width: tbc mm Boxed weight: 1.54 kg Includes pop up waste?: No **Additional comments:**

Product dimensions:



• Overall Height / projection: 101 mm

• Exit reach: 100 mm • Exit height: 49 mm


• Centre distance(s): n/a mm

• Base diameter(s): 50 mm

• Product mounted where: Surface • Recommended hole diameter: 35 mm • Min. fitting depth required: n/a mm

• Max. surface depth: 62 mm

Product flow characteristics:



• Min / Max water pressure: 0.75 / 5.5 bar • Part G mixed flow rate at 3 bar (I/m): 9.68

• Max water temperature: 70° C

• Product flow characteristics: Single flow

• Aerator type: Neoperl honeycomb, laminar, white screen

• Includes output diverter?: N/A

• Control valve type: Single lever (25mm)

• Non return valve position: n/a • Mesh particle filter size: n/a Inlet / outlet size: 1/2" F / M10 • Inlet type / length: Flexi / 345 mm • Shower hose type / length: N/a / n/a

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- $Residues \ of \ liquid \ soaps, \ shampoos \ and \ shower \ foams \ can \ also \ cause \ damage, \ so \ rinse \ with \ clean$ water after using, avoid contact with any abrasives