

Rapture/Rapport/Fervour

Thermostatic Deck Mounted 3 Hole Bath Mixer

Product features:




- Metal construction throughout
- · Thermostatic valve for safety & comfort
- Supplied compete with flexible tail pipes for fast simple fitting
- · Part G compliant for thermostatic bath fillers
- Factory set maximum output temperature 46°C (adjustable)

Packaged properties:

Box length: 440 mm **Box depth:** 395 mm **Box width:** 255 mm **Boxed weight:** 5.23 kg

Includes pop up waste?: No Additional comments:

Product dimensions:



• Overall Height / projection: 213 mm

• Exit reach: 161 mm • Exit height: 107 mm


• Centre distance(s): 100, 100 mm

Base diameter(s): 60, 60, 60 mm
Product mounted where: Deck

Recommended hole diameter: 34-40 mm
 Min. fitting depth required: n/a mm

• Max. surface depth: 30 mm

Product flow characteristics:



- Min / Max water pressure: 0.4 / 5.5 bar
 Part G mixed flow rate at 3 bar (I/m): 29
- Max water temperature: 70° C
- Product flow characteristics: Single Flow
- Aerator type: Flow StraightenerIncludes output diverter?: No
- Control valve type: Thermostatic & 3/4 QT CD ()
- Non return valve position: H&C Inlet
 Mesh particle filter size: 0.60 mm
- Inlet / outlet size: 1/2" M & 3/4" M / 1/2" M & 3/4" M
- Inlet type / length: Flexi / 500 mm
 Shower hose type / length: N/A / N/A

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
 O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Product order code: (AB3006)