

Opulence Basin Pillar Taps



Product features:


- · Metal construction throughout
- Custom designed for lower range pressures
- · Luscious European quality chromium plate finish
- · Fixed spout to prevent accidental water damage
- · Traditional European styling

Packaged properties:

Box length: 255 mm **Box depth:** 95 mm **Box width:** 200 mm **Boxed weight:** 1.64 kg

Includes pop up waste?: No Additional comments:

Product dimensions:



• Overall Height / projection: 140 mm

• Exit reach: 75 mm • Exit height: 55 mm


• Centre distance(s): n/a mm

• Base diameter(s): 45 mm

Product mounted where: Surface
 Recommended hole diameter: 35 mm
 Min. fitting depth required: N/A mm

• Max. surface depth: 40 mm

Product flow characteristics:



Min / Max water pressure: 0.1 / 5.5 bar
Part G mixed flow rate at 3 bar (I/m): 81.5

• Max water temperature: 70° C

• Product flow characteristics: Single flow

Aerator type: Flow straightener
Includes output diverter?: N/A
Control valve type: 1/2" QT CD (8-20)
Non return valve position: n/a
Mesh particle filter size: n/a

Inlet / outlet size: 1/2" M / n/a
Inlet type / length: Fixed / 50 mm
Shower hose type / length: N/a / n/a

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
 O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- Regular cleaning will prevent the build up of lime scale and diff
 After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives