

Gallant

Deck Mounted 4TH Bath Shower Mixer with Shower Handset



Product features:


- Metal construction throughout
- Custom designed for lower range pressures
- · Quarter turn handle action for precise flow control
- Supplied with fixed 3/4" inlets for maximum stability and flow
- Traditional European styling

Packaged properties:

Box length: 410 mm **Box width:** 280 mm **Box depth:** 110 mm **Boxed weight:** 4.98 kg

Includes pop up waste?: No Additional comments:

Product dimensions:



• Overall Height / projection: 244 mm

• Exit reach: 175 mm • Exit height: 140 mm

• Centre distance(s): 100-200 mm


• Base diameter(s): 50 mm

• Product mounted where: Surface

• Recommended hole diameter: 34-44, 28-35, 34-44 mm

Min. fitting depth required: 0 mm
Max. surface depth: 55 mm

Product flow characteristics:



- Min / Max water pressure: 0.4 / 5.5 bar
- Part G mixed flow rate at 3 bar (I/m): bath: 48.75, shower: 21.73

• Max water temperature: 70° C

• Product flow characteristics: Single flow

• Aerator type: White plastic low pressure flow straightener

Includes output diverter?: Yes
Control valve type: 3/4 QT CD (8-20)
Non return valve position: no

Non return valve position: no
Mesh particle filter size: n/a
Inlet / outlet size: 3/4" F / 3/4" F
Inlet type / length: Flexi / 500 mm

• Shower hose type / length: Metal linked / 1.80 m

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
 O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives