Langley Bridge c/w independent Hendon Sidespray

Product Finish: Pewter

Product code: AT3039

EAN13 barcode: 5060048383485



Note: the image shown may not reflect the product finish, chrome finish is typically depicted

Product features:

• Low lead brass construction

• Quarter turn handle action for precise flow control

• Sprayhead functions independently from the tap (spout flow continues if spray activated)

• Supplied with adjustable centres 1/2" inlets, suitable for thicker worktops

• Leading design performance requiring higher pressures


Additional information / Parts included:

Packaged properties:

Box length (mm): 605 Box depth (mm): 85 Box width (mm): 320 Units per outer: 5


Tap only weight (kg): 3.56 Boxed weight (kg): 4.40

Product dimensions:



- Overall Height / projection (mm): 393
- Exit reach (mm): 229Exit height (mm): 262
- **Centre distance(s):** 203mm nominal +/- 50mm (153-253mm)
- Base diameter(s) (mm): 45
- Recommended hole diameter (mm): Ø 35
- Max. surface depth (mm): 85
- Spout diameter (mm): 20Spout aerator size: M20

Product flow characteristics:



- Min / Max water pressure (bar): 1.00 / 5.5
- Recommended / Max water temperature: 46°C / 70°C
- Part G Mixed flow rate at 3 bar (litres / min): 17.86
- Control valve type: Ceramic disc QT
- **Product flow characteristics:** Single flow
- Non-return/Check valve(s): Integral to H & C inlets and sprayhead
- Aerator type: Neoperl SLIM AIR CCSLC STD flow class V
- Accepts revolve / spray areator: No
- Spout connection method: Locking collar
- Tail pipe inlet / outlet size: 3/4" BSP male / 1/2" BSP Male
- Inlet pipe type / length (mm): fixed threaded inlets / 105

Care instructions summary:

- ·Clean the product regularly using a mild washing up liquid, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt

 After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):
.Materials and workmanship defects warranted for 5 years
.Valves and working parts warranted for 5 years
.Surface warranty defects warranted for 5 years
.O-rings, hoses & gaskets warranted for 5 years

