

Product features:

- Metal & ABS construction
- Single lever control for effortless single handed control
- Minimalist planate design form
- 1/4 turn lock on diverter to handheld showerhead


Packaged properties:

Box length (mm): 1150 **Box depth(mm):** 240
Box width(mm): 495 **Boxed weight (Kg):** TBC

Includes pop up waste?: No


Additional comments:
ABS showerhead

Product dimensions:



- **Product mounted where:** Floor
- **Recommended hole size:** N/A mm
- **Overall Height / projection:** 990 mm
- **Exit reach:** 285 mm
- **Exit height:** 850 mm
- **Base size:** 150 mm
- **Inlet centre distance(s):** N/A mm
- **Min. fitting depth required:** 70-110 mm
- **Max. surface depth:** N/A mm

Product flow characteristics:



- **Min / Max water pressure (bar):** 1.50* / 5.50
*Detailed minimum pressure requirements for this product: Bath 1.5, Shower 0.75 (bar)
- **Part G max. mixed flow rate at 3 bar (l/m):** 13.57
- **Inlet connection type / length:** Fixed / 100 mm
- **Inlet (plumbing connection) / outlet size:** 1/2M / 1/2"M
- **Product flow characteristics:** Single flow
- **Non return valve(s) supplied or position:** No
- **Aerator type:** Neoperl, honeycomb light blue
- **Control valve type:** Single lever (35mm)
- **Includes output diverter?:** Yes
- **Inlet meshed particle filters included:** No
- **Shower hose type / length:** Smoothflex / 1.50 m

Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives