

DD940BK

Induction Downdraft Extractor



PLASMA

With this product, you have the option to use our new Plasma technology. This allows you to recirculate the air with this very efficient odour removal process. The Plasmabox and charcoal filter are cleverly hidden away in the plinth below the cabinets, so no need to duct the product to the outside wall. You can also install all the pipework into a 300mm wide carcase space allowing for a lot more use of the kitchen cupboard when compared to a conventional downdraft.

The Plasma technology also extends the life of the charcoal filter from around 6 months to 5 years, 1 filter will last the equivalent of 10 without the Plasmabox.

DIMENSIONS

w: 900mm

PERFORMANCE

Energy Class	A+
Max. extraction	650m ³ /h
Max. Noise level	64dB
Grease absorption	A
Fluid Dynamic Efficiency	A
Annual consumption	32,3

FINISH AVAILABLE

Black Glass

COOKING OUTPUT

Induction Zones
- 190 x 220mm - 3.7kW

FEATURES

Hob

- Frameless
- Can be flush mounted
- Slider touch control
- Large cooking area
- 10 Power level digital display for each zone [0-9 plus Booster]
- Booster function on all zones, including Auto Boost mode
- Bridge function to combine 2 zones
- Timer for each zone / minute minder
- Memory recall function
- 3 preset temperatures settings (bake 42°C, keep warm 70°C, boil control 92°C)
- Pause function
- Child safety lock
- Residual heat indicators
- Automatic safety shut-off
- Anti-overheat
- Auto pan detection

Downdraft

- Touch control
- 4 Speeds
- Auto timer
- Aluminium grease filters
- Required ducting size 150mm
- Plinth motor included
- Optional plasma filter

OPTIONAL EXTRAS

- Recirculation kit CAP57CF
- PLASMABOX

ELECTRICAL CONNECTION

- Rated load 7.7kW
- Fuse rating 32Amp

