



PIA'13 PRODUCT INNOVATION AWARD WINNER

KWC-No.	Finish
10.201.122.000	chrome
A 8 7/16", flexible connection hoses, plug power supply	
10.201.122.127	splendure™ stainless steel
A 8 7/16", flexible connection hoses, plug power supply	

Kitchen with luminaqua® LED-technology



Single-lever mixer

- Lever installation only possible on the right side
 - Child safety: cold water flow in lever position towards the front
- gap between wall and centre of mounting hole min. 1 5/8"
- Covered pull-out spray
 - ergonomic spout alignment, shape and handling
 - KWC JETCLEAN technology
 - Neoperl® Cascade®
 - automatic diverter reset
 - integrated ON/OFF push-button with automatic shut-off after 30 minutes
 - up to 19 1/16" pull-out length
 - hose surface to fit faucet surface
- Hose guide, swiveling 270°
- KWC cartridge S 25
 - with ceramic discs
 - flow rate and temperature continuously variable
- Flexible connection hoses 3/8" compression
- Fastening by means of threaded sleeve M33 x 1.5
- Mounting hole size ø1 3/8"
- Delivery includes:
 - Plug power supply 100-240 V / operating voltage 6.75 V / cable length 43 5/16"

Flow rate max 1.75 gpm (60 psi)
Flow rate needle spray max 1.75 gpm (60 psi)