OP TS1503 CH C

COMMERCIAL Shower Range TS1503 Opac Concealed Shower Valve



| F | Д | a | t١ | п | r | ۵ | s: |
|---|---|---|----|---|---|---|----|
| | v | ч | G, | м | | · | J. |

- Anti-vandal stainless steel removable concealing plate
- Easy access self-isolating serviceable filters
- Single sequential control for both temp and flow
- High performance even at low pressures
- Check valves and serviceable filters as standard

Product Certifications:



Expiry Date : 30/12/2023 Cert Number : 1812703



Cert Number : NSF2014/0718 Expiry Date : 06/07/2023





For more products, visit our website: http://www.bristan.com



| Specification | | | | | | | |
|--------------------------------------|--------------------------|--|--|--|--|--|--|
| Finish/Colour: | Chrome | | | | | | |
| Main Construction Material: | Brass | | | | | | |
| No of Controls: | 1 | | | | | | |
| Shower Type: | Concealed Shower Valve | | | | | | |
| Shower Head Type: | N/A | | | | | | |
| Valve/Cartridge Type: | Thermostatic | | | | | | |
| Maximum Hot Water Supply Temperature | 80 | | | | | | |
| Maximum Static Pressure: (bar) | 8 | | | | | | |
| Plumbing System Suitability: | All, Preferably Balanced | | | | | | |
| Working Pressure Range: bar | 0.2-5 | | | | | | |
| Connection Inlet: | 15mm Compression Elbows | | | | | | |
| Connection Outlet: | 1/2" BSP | | | | | | |
| Isolation Valve Included: | No | | | | | | |
| Check Valve Included: | Yes | | | | | | |

Dimensions (measurements in mm)





| Flow Rates (I/min) | | | | | | | | | |
|-----------------------|--|-----|-----|-----|-----|-----|--|--|--|
| System Pressure (bar) | | 0.5 | 1 | 2 | 3 | 5 | | | |
| Flow Limiters Fitted | | 6.8 | 7.1 | 8.1 | 8.6 | 9.0 | | | |

TECHNICAL DATA SHEET



