SOLO-NM LL

SOLO Tap Range

Solo Non-Thermostatic Healthcare Tap with Long Lever Handle



| _ | | | | | | | s: |
|---|------------|--------------|---|----|------------------|----------|----|
| _ | $^{\circ}$ | \mathbf{a} | т | 11 | \boldsymbol{r} | \frown | С. |
| | ᆫ | a | u | u | | C | Э. |
| | | | | | | | |

- Pressure balancing basin mixer tap with long lever handle
- Maximum temperature stop is adjustable for user safety and comfort
- Removable spout to aid infection control regimes
- A choice of fully draining or laminar flow outlets supplied
- Smooth machined internal waterways to help limit the build-up of bacteria within the tap body

Product Certifications:



WRAS Certificate No: 1711006


WRAS Expiry Date: 30/11/2022

For more products, visit our website: http://www.bristan.com



| Specification | | | | | | |
|-----------------------------------|--------------------------|--|--|--|--|--|
| Style: | Contemporary | | | | | |
| Product Type: | Commercial | | | | | |
| Main Construction Material: | Brass | | | | | |
| Mount Type: | Deck Mounted | | | | | |
| Handle Type: | Lever | | | | | |
| Connection Inlet: | 15mm Compression | | | | | |
| Connection Outlet: | M24 Flow Straightener | | | | | |
| Number of Tap Holes: | 1 | | | | | |
| Valve/Cartridge Type: | 35mm Cartridge | | | | | |
| Plumbing System Requirements: | All | | | | | |
| Working Pressure Range: | Min 0.5 Bar, Max 5.0 Bar | | | | | |
| Maximum Hot Water Temperature: °C | 80 | | | | | |
| Maximum Dynamic Pressure: (bar) | 5 | | | | | |
| Maximum Static Pressure: (bar) | 10 | | | | | |
| Flow Type: | Single Flow | | | | | |
| Flow Rate: (I/min @ 3 bar) | 5.3 | | | | | |
| Isolation Included: | No | | | | | |
| | | | | | | |

Dimensions (measurements in mm)



| Flow Rates (I/min) | | | | | | | | | | |
|-----------------------|-----|-----|-----|-----|-----|--|--|--|--|--|
| System Pressure (bar) | 0.5 | 1 | 2 | 3 | 5 | | | | | |
| SOLO-NM LL | 3.5 | 4.5 | 5.1 | 5.3 | 6.8 | | | | | |

TECHNICAL DATA SHEET



