

**Serie | 4, Wall-mounted cooker hood,
90 cm, Stainless steel
DWQ96DM50B**

A



Slim Pyramid hood: performance and matching design in your kitchen.

- **TouchSelect control:** quick touch-control selection of desired settings and light.
- An impressive extraction rate of 642 m³/h ensures this hood will have your kitchen odour free in no time.
- **Silent:** maximum extractor performance with little noise

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-912/582-1022
Height of product, without chimney (mm) :	94
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	12.180
Type of control :	Electronic
Maximum output air extraction (m ³ /h) :	389
Boost position output recirculating (m ³ /h) :	372
Maximum output recirculating air (m ³ /h) :	308
Boost position air extraction (m ³ /h) :	642
Number of lights (Stck) :	2
Noise level (dB(A) re 1 pW) :	61
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable aluminium
EAN code :	4242005051243
Connection rating (W) :	220
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	60; 50
Plug type :	GB plug
Installation type :	Wall-mounted

Optional accessories

- DHZ1225 : Chimney extension 1000 mm
- DHZ1235 : Chimney extension 1500 mm
- DHZ9550 : Brushed steel back panel
- DHZ9551 : Brushed steel back panel
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6200 : CleanAir Recirculation Kit
- DWZ0DX0A0 : Active carbon filter
- DWZ0DX0U0 : Recirculating kit
- DWZ0XX0I0 : Integrated CleanAir Recirculation Kit
- DWZ0XX0J0 : Integrated CleanAir Recirculation Kit
- DZZ0XX0P0 : CleanAir act.carbon filter regenerative



Serie | 4, Wall-mounted cooker hood, 90 cm, Stainless steel DWQ96DM50B

Slim Pyramid hood: performance and matching design in your kitchen.

Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 389 m³/h
Intensive 642 m³/h
- Noise max. Normal Level: 61 dB*

Features

- TouchControl with Electronic display
- LED
- 3-stage + intensive
- 2 x LM3-01_LED_1,5W
- Colour Temperature: 3500 K
- 6 min.
- 3 PC
- wall

Design

- Stainless steel
- Pyramidal slimline
- Wall mounted chimney hood
- touch control
- Electronic

Performance/technical information

- Ducted/Recirculating operation
- Recirc. kit or clean air kit
- Max. extraction rate: 642 m³/h
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 389 m³/h
Intensive 642 m³/h
- Extraction rate in recirculation mode:
Max. normal use: 308 m³/h
Intensive: 372 m³/h
- Noise max. Normal Level: 61 dB*
- Noise level according to EN 60704-3 and EN 60704-2-13
exhaust air:
Max. normal use: 61 dB(A) re 1 pW (48 dB(A) re 20 µPa sound
pressure)
Intensive: 70 dB(A) re 1 pW (57 dB(A) re 20 µPa sound
pressure)
- Noise levels in recirculation mode:
Max. normal use: 71 dB(A) re 1 pW (58 dB(A) re 20 µPa sound
pressure)
Intensive: 75 dB(A) re 1 pW (62 dB(A) re 20 µPa sound
pressure)
- Power rating: 220 W
- Light Intensity: 214 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 676-1006 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 676-1116 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):
744 x 900 x 500 mm - mounting with outer chimney
874-1204 x 900 x 500 mm - mounting with telescopic chimney
- Energy Efficiency Class: A (at a range of energy efficiency
classes from A+++ to D)
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 42.4 kWh/year*

Optional accessories

- Recirculating kit

* In accordance with the EU-Regulation No 65/2014

