

Serie | 6, Canopy cooker hood, 70 cm,  
Stainless steel  
DHL785CGB



Optional accessories

- DHZ5316 : Active carbon filter  
DHZ5605 : Recirculating kit  
DSZ4681 : CleanAir active carbon filter  
DSZ4683 : CleanAir Recirculation Kit  
DWZ0IT0P0 : CleanAir act.carbon filter regenerative

Canopy cooker hoods are designed to be fully integrated for more flexibility when planning your kitchen.



- An impressive extraction rate of 730 m3/h ensures this hood will have your kitchen odour free in no time.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.

Technical Data

Typology :	Traditional
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	150
Required niche size for installation (HxWxD) :	418mm x 676mm x 264mm
Minimum distance above an electric hob :	500
Minimum distance above a gas hob :	650
Net weight (kg) :	9.020
Type of control :	Electronic
Maximum output air extraction (m3/h) :	630
Boost position output recirculating (m3/h) :	310
Maximum output recirculating air (m3/h) :	300
Boost position air extraction (m³/h) :	730
Number of lights (Stck) :	2
Noise level (dB(A) re 1 pW) :	66
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242002831206
Connection rating (W) :	277
Current (A) :	3
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation type :	Built-in



**Serie | 6, Canopy cooker hood, 70 cm,  
Stainless steel  
DHL785CGB**

*\* In accordance with the EU-Regulation No 65/2014*

**Canopy cooker hoods are designed to be fully integrated for more flexibility when planning your kitchen.**

---

**Key Information**

- Electronic control via Soft touch button control

**Design**

- For installation in a kitchen cabinet
- 70 cm wide
- Brushed steel

**Features**

- Soft touch button control with Electronic display
- 3 power levels & intensive setting
- Automatic intensive revert (6mins)
- Rim ventilation
- 2 x 1W LED
- 2 removable metal grease filter cassettes
- Filter cover stainless steel, Removable metal grease filters

**Performance/technical information**

- Suitable for ducted or recirculating operation
- Extraction rate exhaust air according to EN 61591:  
max. normal use 630 m<sup>3</sup>/h, intensive 730 m<sup>3</sup>/h
- Power rating: 277 W
- Noise level according to EN 60704-3 and EN 60704-2-13  
exhaust air:  
Max. normal use: 66 dB(A) re 1 pW (52 dB(A) re 20 µPa sound pressure)  
Intensive: 69 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)
- Noise max. Normal Level: 66 dB\*
- Average Energy Consumption: 104.2 kWh/year\*
- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: C\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: D\*
- Dimensions exhaust air (HxWxD): 418-418 x 700 x 300 mm
- Dimensions recirculating (HxWxD): 418-418 x 700 x 300 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Light Intensity: 244 lux
- Colour Temperature: 4000 K

**Accessories**

- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed

**Serie | 6, Canopy cooker hood, 70 cm,  
Stainless steel  
DHL785CGB**

