

**Serie | 2, Wall-mounted cooker hood,  
90 cm, clear glass  
DWG94BC50B**



**Hood with glass design: performance  
combined with straight glass design  
matching your kitchen.**

- **Push buttons:** simply change the desired power level settings with mechanic control.
- An impressive extraction rate of 365 m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- **Silent:** maximum extractor performance with little noise

**Technical Data**

|                                                        |                    |
|--------------------------------------------------------|--------------------|
| Color chimney :                                        | Stainless steel    |
| Typology :                                             | Chimney            |
| Approval certificates :                                | CE, VDE            |
| Length of electrical supply cord (cm) :                | 130                |
| Height of the chimney (mm) :                           | 576-906/576-998    |
| Height of product, without chimney (mm) :              | 59                 |
| Minimum distance above an electric hob :               | 550                |
| Minimum distance above a gas hob :                     | 650                |
| Net weight (kg) :                                      | 14.681             |
| Type of control :                                      | mechanical         |
| Number of speed settings :                             | 3                  |
| Maximum output air extraction (m <sup>3</sup> /h) :    | 365                |
| Maximum output recirculating air (m <sup>3</sup> /h) : | 195                |
| Number of lights (Stck) :                              | 2                  |
| Noise level (dB(A) re 1 pW) :                          | 64                 |
| Diameter of air outlet (mm) :                          | 150 / 120          |
| Grease filter material :                               | Washable aluminium |
| EAN code :                                             | 4242005051175      |
| Connection rating (W) :                                | 100                |
| Current (A) :                                          | 10                 |
| Voltage (V) :                                          | 220-240            |
| Frequency (Hz) :                                       | 60; 50             |
| Plug type :                                            | GB plug            |
| Installation type :                                    | Wall-mounted       |

**Optional accessories**

- DHZ1225 : Chimney extension 1000 mm
- DHZ1235 : Chimney extension 1500 mm
- DHZ9550 : Brushed steel back panel
- DHZ9551 : Brushed steel back panel
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6200 : CleanAir Recirculation Kit
- DWZ0DX0A0 : Active carbon filter
- DWZ0DX0U0 : Recirculating kit
- DWZ0XX0I0 : Integrated CleanAir Recirculation Kit
- DWZ0XX0J0 : Integrated CleanAir Recirculation Kit
- DZZ0XX0P0 : CleanAir act.carbon filter regenerative



4 242005 051175

## Serie | 2, Wall-mounted cooker hood, 90 cm, clear glass DWG94BC50B

**Hood with glass design: performance combined with straight glass design matching your kitchen.**

### Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 365 m<sup>3</sup>/h
- Noise max. Normal Level: 64 dB\*

### Features

- Push button control
- 3 power levels
- 2 x 1.5W LED light
- Colour Temperature: 3500 K
- 2 removable metal grease filter cassettes
- Designed for wall mounted installation

### Design

- Brushed steel glass canopy
- Glass design
- Chimney extractor hood
- Mechanical

### Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Max. extraction rate: 365 m<sup>3</sup>/h
- Maximum extraction rate exhaust air 365 m<sup>3</sup>/h according to EN 61591
- Extraction rate in recirculation mode:  
Max. normal use: 195 m<sup>3</sup>/h
- Noise max. Normal Level: 64 dB\*
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW (51 dB(A) re 20 µPa sound pressure)
- Noise level in recirculation mode:  
Max. normal use: 66 dB(A) re 1 pW (53 dB(A) re 20 µPa sound pressure)
- Power rating: 100 W
- Light Intensity: 91 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 900 x 525 mm
- Dimensions recirculating (HxWxD): 635-1075 x 900 x 525 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
703 x 900 x 525 mm - mounting with outer chimney  
833-1163 x 900 x 525 mm - mounting with telescopic chimney
- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 53.1 kWh/year\*

### Optional accessories

- Recirculating kit

\* In accordance with the EU-Regulation No 65/2014

