Technical Specification Sheet	• •	•
Attenzi / Tribezi Tank		
	REGI	NOX
3 in 1 Boiling Hot Water Tank		NOA
	Tank Specification	
	Finish	Black Coating
	Body	Stainless Steel
	Connections	Inlet ¼" push fit, Outlet 2 step Plastic barb Connector Pushes and locks (JG snap
	Push Fit Connections	3/8" JOHN GUEST TYPE SNAP FIT GROOVE SHAFT
	Tank Dimensions	
REGINOX	Height (mm)	263
	Width (mm)	172
	Length (mm)	252
	Tank Info	
<u>→</u> 172 → 172 → 252 → 1	1.5Kw element- 3L Tank	Filter Change reminder and
	Capacity	Eco Mode.
	Improved insulation for better thermal energy saving properties and less boiling noise.	
	Additional Improvments	
	Filter has had a higher phosphate level added to help improve slightly the water quality going to the tank, the filter will help against hard water / LimeScale but will not stop it! Improved Thermistor manufactured using titanium, helping lower lime scale build up.	
Additional Features/Benefits	Universal Quick Fit Connections on tank make it even	
6 Preset Temperatures on tank - 98 Degrees Max, 97 / 95 / 90 / 85 and 75 degrees	simper to install Box Dimensions	
Suitable for all plumbing systems	Weight (kg)	4.3
Eco mode and Filter reminder	Box Dimensions (mm)	Height 465mm,Width
Warranty	Packed Weight (kg)	10
2 years manufacturing on tank, 6 months on Filter (Filter must be	Cerfiticates	
changed every 3-6 months to ensure this doesn't invalidate warranty	Tank	
on tank) Customers must register the warranty as per the info on the	Idlik	Тар
tank / card Care & Maintenance Reginox recommends cleaning your tap regularly with non- abrasive cleaners. Warm, soapy water would be best.	APPROVED PRODUCT	kiwa

REGINOX UK LTD Units 1-4 Radnor Park Trading Estate, Back Lane, Congleton, Cheshire, CW12 4XJ www.reginox.co.uk | 01260 280033 | sales@reginox.co.uk